

# caroma®

CI/SfB	(74.1)	g3
Date	October 2016	

Supersedes all previous issues

## Sydney Smart 305 One Piece Easy Height Elongated

**1.28/0.8 gpf (4.8/3 lpf) Water Saving Dual Flush High Efficiency Toilet (HET)  
One-Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet**



HIGH EFFICIENCY TOILET  
**HET**



**c-UPC®**  
IAPMO listed for USA & Canada

# Sydney Smart 305 One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3 lpf) Dual Flush HET

**One Piece Ultra Low Flush (ULF)  
Vitreous China Washdown Toilet**



A modern concept one piece toilet featuring an integral **1.28/0.8 gpf (4.8/3 lpf) Sydney Smart 305 One Piece Easy Height Elongated** dual flush high efficiency toilet (HET) designed to provide a seat height of between 17" to 19" (432 to 482mm) measured to the top of the toilet seat for disabled persons. The versatility of the **Sydney Smart 305 One Piece Easy Height Elongated** integral toilet makes it ideal for use by both the ambulant persons with disabilities and wheel-chair users. Designed with smooth rounded contours for easy cleaning. **Important:** The Sydney Smart 305 One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Toilet:** **Sydney Smart 305 One Piece Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.
- Outlet:** Floor mounted 12" (305mm) elongated outlet connection.
- Tank:** The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications, features low profile push buttons.
- Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the tank, recommended for use in heavy duty commercial areas. Code No. 750109.
- Water Control Valve:** **Standard Bottom Entry** – available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.
- Weight:** 84 lbs (38 kgs)
- Fixing:** The one piece toilet is bonded to the floor with an approved acetic-cured silicon caulking and fixed with corrosion resistant screws and closet bowl guard washers.
- Seats:** Caroma **Soft Close, Detachable Seat Model 326611W Included** White only.
- Colors:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.
- Dimensions:**

