

# caroma®

CI/SfB	(74.1)	g3
Date	October 2008	

Supersedes all previous issues

## Caravelle 270 Easy Height Round Front Plus

# 2.4.2

**1.6/0.8 gpf (6/3 l) Water Saving Dual Flush High Efficiency Toilet (HET)  
Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet**



HIGH EFFICIENCY TOILET  
**HET**



**c-UPC®**  
IAPMO listed for USA & Canada

# Caravelle 270 Easy Height Round Front Plus 1.6/0.8 gpf (6/3 l) Dual Flush HET

## Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet



Caroma Raised Push Button Option

A modern concept close coupled **1.6/0.8 gpf (6/3 l) Caravelle 270 Easy Height** dual flush washdown toilet installation designed to provide a seat height of between 17" to 19" (430 to 485mm) measured to the top of the toilet seat. The closet bowl has been designed with rough-in of **10" (255mm) to 12" (305mm)** provided by plastic offset outlet connector option. The tank incorporates the high performance outlet valve which has been specially developed with the 270 Easy Height Round Front Plus bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.6/0.8 gpf (6/3 l) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important.

**Closet bowl:** **270 Easy Height Round Front Plus** 1.6/0.8 gpf (6/3 l) full flush washdown closet bowl with open flushing rim.

**Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.

**Tank:** **Caravelle Tank** – has a free fitting lid and is suitable for domestic and light commercial applications. **Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the tank, recommended for use in heavy duty commercial areas. Code No.413276. High profile buttons option for visually impaired Code No. 405067.

**Weight:** 94 lbs (43 kg).

**Water Control Valve:** **Standard Bottom Entry Tank** – available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.

**Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.

**Seats:** The following Caroma seats are recommended: **Detachable** Code No. 301032, **Easy Closing** Code No. 326222, **Standard** Code No. 326707, and **Wooden** Code No. 326606.

**Colors:** White and biscuit.

**Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

