

caroma®

CI/SfB	(74.1)	g3
Date	November 2007	

Supersedes all previous issues

Royale 270

1.6/0.8 gpf (6/3 l) Water Saving Dual Flush High Efficiency Toilet (HET)

Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet

2.7.1



HIGH EFFICIENCY TOILET
HET

c-UPC®
IAPMO listed for USA & Canada

Royale 270
1.6/0.8 gpf (6/3 l)
Water Saving
Dual Flush High
Efficiency Toilet (HET)

Two Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept close coupled **1.6/0.8 gpf (6/3 l)** dual flush toilet featuring unique two button activation providing substantial water saving compared to standard toilets and adjustable rough in and smooth rounded contours for easy cleaning. The closet bowl has been designed with rough in of **10" (255mm)** to **12" (305mm)** provided by plastic offset outlet connector option. The overall length from the finished wall is 29^{3/4"} (760mm). The tank incorporates the high performance outlet valve which has been specially developed with the Royale 270 toilet to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.6/0.8 gpf (6/3 l) dual flush system the toilet is suitable for multi purpose applications where **water conservation** is important.

- Closet Bowl:** **Caravelle 270** 1.6/0.8 gpf (6/3 l) full flush washdown closet bowl with open flushing rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) and 12" (305mm) rough in.
- Tanks:** **Royale 2000 Tank** – has a free fitting lid and is suitable for domestic and light commercial applications. **Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the tank, recommended for use in heavy duty commercial areas Code No.413276.
- Weight:** 78 lbs (35 kg).
- Water Control Valve:** **Standard Bottom Entry Tank** – available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Seats:** The following Caroma seats are recommended: **Caravelle** Code No.301032, **Royale** easy closing Code No. 326222, **Royale** Code No.326707 and **Colonial Wooden** Code No.326606.
- Colors:** White and biscuit.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Royale 270	Code No.
Tank	LH inlet 624530
Bowl	609159

HIGH EFFICIENCY TOILET

HET

c-UPC®

IAPMO listed for USA & Canada

Note: All height dimensions to underside of closet bowl, make allowance for bedding.

Screw fixing: The closet bowl should be bedded with an approved silicon caulking and fixed with corrosion resistant screws and closet bowl guard washers. Use Caroma screw fixing kit. Code No. 601150.