

Price List

CANADA
OCT1 2021






At Caroma, design is our lifeblood.

Caroma products are beautiful to look at, brilliantly efficient and a pleasure to use. Our team of talented designers understands the Caroma customer better than anyone. At the same time, they are at the forefront of local and international shifts in design to ensure that the products we bring to market match North American expectations and their signature way of life.

Caroma products are renowned for the simplicity of their form. Yet beneath the clean lines lie complex design decisions, meticulous engineering and a relentless pursuit of quality that we never shy away from. We have some of the highest quality standards in the world. Every stage, from design conception to delivery and servicing is carefully and methodically managed and executed. Caroma has always operated with this holistic view. Our Research and Development has developed a global reputation for sustainability and design that reflects our pride in going above and beyond North American standards. That's how we've built a reputation for quality that you can depend on.


Caroma. Conservation without Compromise





inspiring

bathroom design for 70 Years



The Power of Performance



“Virtually Unblockable” – This phrase has become overused yet the problem of clogging toilets remains, especially in challenging environments like the hospitality industry. We can’t say that it is impossible to clog a Caroma® toilet because let’s face it, if anyone really set their mind to it anything is possible. But the fact is, you’d have to work at it!

There is a reason why 5-Star hotels across North America have been changing out relatively new toilets and replacing them with Caroma® models. Actually, there are lots of good reasons! That Caroma toilets are beautiful and save vast amounts of water and reduce water bills is the starting point. But there is much more to the Caroma story. Every hotel that has retrofitted with Caroma® toilets has reported in follow up studies that room clogging emergencies have all but disappeared. Eliminating hundreds of costly, messy and embarrassing clogging emergencies a year has made Caroma® a well respected name among hotel managers. And If Caroma can handle the most challenging environments so successfully, imagine how well it can perform in your home.

- **Caroma® Smart Technology Boasts 1.28/0.8gpf (4.8/3 lpf)**
- **One of the Lowest Consumption HET’s on the Market with an Average 0.9gpf (3.6L)**
- **Oversized Fully Glazed Trapway that Virtually Eliminates Blockages**
- **ADA Compliant Models Available**
- **Reliable Construction and Superior Quality**
- **Easy to Install, Even Easier to Maintain**

Old Style Siphonic Flush

With typical North American toilets, most of the flush volume is used to create a siphon and ‘pull’ water from the bowl. To enable the siphonic action to start, the trap size must remain small. This is where clogging occurs.

average
1 7/8" - 2 3/8" trap




caroma®

www.caromausa.com



Siphonic vs. Caroma® Dual-flush with WashDown



Caroma® Dual-flush with WashDown

Flush volume is used to 'push' waste from the bowl and into the drain line.

10-12" Adjustable rough-in and Smart Connect on select models.

Caroma® toilets include a massive trapway area which is nearly double that of the industry standard.

Caroma® Offers a Free Cost Benefit Analysis of Water and Energy Usage

At Caroma®, we know that tangible results are the most important part of your business. That is why we are committed to providing the confidence you need to make the smartest choice, and deliver the most powerful results. Caroma® is proud to offer an exclusive service for every project: our complimentary Cost Benefit Analysis of Water and Energy Usage. Our dedicated team of engineers and water conservation specialists will partner with your site management group to develop a comprehensive site analysis for any Caroma® project, including the resource and cost savings generated by your switch to Caroma®'s Smart Technology.

Our free Cost Benefit Analysis of Water and Energy Usage is your opportunity to truly see the impact of Caroma®, and go beyond the basics of conservation. Protection of local water resources is simply the beginning. By choosing Caroma® products, Smart Technology and intelligent resource management paves the way for significant savings in energy costs, sewer charges, and environmental damages, delivering substantial savings for your business, for results you can see. Savings from the start – only from Caroma®.



POP2-150310 www.caromausa.com

Smart Connect™


Simply the best.

From a design perspective, 'simple' is often the most challenging objective. Smart Connect™ was designed to simplify installations and make them work - beautifully. With Smart Connect™, a unique off-set adaptor fits neatly over your sewer rough-in, containing the mess of the wax ring. Your Caroma® bowl fits easily over top of the connector, and is tightened by discreet bolts on the side of the bowl. *Perfectly Simple!*



- **CLEAN** - Adaptor covers the mess of wax ring, making future Caroma installations clean, simple and easy!
- **FLEXIBLE** - The unique Adaptor can accommodate a 10" to 12" sewer rough-in incrementally and allows for approximately 1" of lateral adjustment.
- **EASY** - Simply install the adaptor over your wax ring and install toilet bowl over top. Toilet is stabilized through hidden side bolts.
- **PRECISE** - You are able to check that you have a perfect seal every time before the bowl is even placed! Plumbers love it!
- **BEAUTIFUL** - Bolt holes are small and discreet and concealed with small color coded panels.
- **NO DRILLING** - No need to ever drill into the flooring, even for commercial applications

Cube Invisi™ Series II Wall Hung In-Wall System



Description	Code	Weight (lbs.)	CDN. List
Cube Invisi™ Cube bowl	604300W	57	\$863
Option 1: Tank, wall-hung carrier, and connector for in-wall, in-duct, or in-ceiling installations	237061	32	\$849
Option 2: In-wall tank, carrier and connector for under-counter installations	237062	33	\$899
Cube easy close seat	300024W	7	\$199

Please see following page for button options.

Somerton Invisi™ Series II Wall Hung In-Wall System



Description	Code	Weight (lbs.)	CDN. List
Somerton Invisi™ Somerton elongated bowl MaP Premium 1000 g.	604100W	57	\$563
Option 1: Tank, wall-hung carrier, and connector for in-wall, in-duct, or in-ceiling installations	237061	32	\$849
Option 2: In-wall tank, carrier and connector for under-counter installations	237062	33	\$899


Please see following page for button options. Seat Options are shown in Seat Section of Price Book.

Tank hidden behind the wall for maximization of valuable floor space and cleanliness. Features HET 1.28/0.8 gpf dual-flush system.

Available in standard in-wall tank or undercounter tank installations.


Somerton is ADA Compliant with Bowl Height of 16 to 17" and is MaP Premium labelled at 1000g

Cube Invisi™ Series II



Bowl Height: Bowl adjustable to 17"

Somerton Invisi™ Series II



Bowl Height: Bowl adjustable to 17"

Optional Extras for Invisi Systems


Description	Code	CDN. List
Remote mounting box kit (for remote or induct mounting- <i>Requires blank access panel</i>)	237006	\$79
4M (13ft) pneumatic hose	237702	\$18



Invisi™ Series II round dual-flush custom button set

Description	Code	Weight (lbs.)	CDN. List
Round dual-flush	237013C (chrome)	1	\$108
Custom mount button set	237013S (satin)	1	\$120

(Note: Requires 237702 pneumatic tube, purchased separately)



Invisi™ Series II round dual-flush plate & button set

Description	Code	Weight (lbs.)	CDN. List
Round dual-flush	237010W (white)	1	\$113
plate and button set	237010C (chrome)	1	\$122
	237010S (satin)	1	\$129



Invisi™ Series II ADA dual-flush plate & raised button set

Description	Code	Weight (lbs.)	CDN. List
ADA dual-flush plate	237011C (chrome)	1	\$133
and raised button set	237011S (satin)	1	\$151



Invisi™ Series II rectangular dual-flush custom button set

Description	Code	Weight (lbs.)	CDN. List
Rectangular dual-flush	237023C (chrome)	1	\$108
custom mount button set	237023S (satin)	1	\$120

(Note: Requires 237702 pneumatic tube, purchased separately)



Invisi™ Series II blank access panel to allow tank access when buttons are located elsewhere

Description	Code	Weight (lbs.)	CDN. List
Blank access panel	237024C (chrome)	1	\$104
	237024S (satin)	1	\$117



Invisi™ Series II metal rectangular dual-flush plate & button set

Description	Code	Weight (lbs.)	CDN. List
Metal rectangular	237020C (chrome)	1	\$229
dual-flush plate	237020S (satin)	1	\$245
and button set	237020MB (MB)	1	\$255



Brisbane 270 Round Front Plus Standard Height

Driven by Design. The clean lines of Caroma®'s Brisbane 270 High Efficiency toilet (HET) illustrate that powerful performance does not have to sacrifice style.

- Utilizes 1.6/0.8 gpf (6/3 lpf)
- Caroma®'s signature trapway is twice the size of the industry average, virtually eliminating clogs
- Large fully-concealed trapway.
- Extreme installation adjustability: Can accommodate 10" to 12" rough in incrementally, and allows for approx. 1" of lateral movement.
- Bowl height 15½"
- Map Certified and Watersense Labelled
- Requires Brisbane 301033W Soft Close Seat

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Brisbane Tank	810266W	29	\$201
Brisbane 270 Bowl	833900W	77	\$325
Brisbane Soft Close Seat	301033W	5	\$101
Tank and Bowl and Seat		111	\$627

Additional Highlights



Signature Trapway

- At more than twice the size of standard North American trapways, Caroma® eliminates clogging.*

*It is not waste that typically clogs toilets, it is paper products. The massive Caroma® trapway has been tested for decades in extreme conditions all over the world with almost perfect success! Clogging a Caroma® toilet would require an unreasonably excessive amount of paper.


Brisbane 270 Round Front Plus 1.6/0.8 gpf (6/3 l) Dual Flush HET

Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet



A modern concept close coupled **1.6/0.8 gpf (6/3 l) Brisbane 270** dual flush toilet featuring unique two button activation providing substantial water saving compared to standard toilets. Adjustable rough-in and smooth rounded contours for easy cleaning. The closet bowl has been designed with rough-in of **10" (255mm)** to **12" (305mm)** provided by plastic offset outlet connector option. The tank incorporates the high performance outlet valve which has been specially developed with the Brisbane 270 bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.6/0.8 gpf (6/3 l) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important.

- Closet Bowl:** **Brisbane 270** 1.6/0.8 gpf (6/3 l) full flush washdown closet bowl with open flushing rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.
- Tank:** **Brisbane Tank** – has a free fitting lid and is suitable for domestic and light commercial applications. **Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the tank, recommended for use in heavy duty commercial areas. Code No. 413276.
- Weight:** 111 lbs (50 kg).
- Water Control Valve:** **Standard Bottom Entry Tank** – available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Seat:** **Brisbane** seat Code No. 301033.
- Color:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.






Caravelle Smart 270 One Piece Easy Height Elongated

Inspired by Innovation. The redesigned Caravelle Smart 270 One Piece High Efficiency Toilet (HET) exemplifies Caroma®'s dedication to simple beauty and Smart Design.

- 1.28/0.8 gallon (4.8/3 litre) Top Mounted two button dual flush toilet-
- Large fully glazed, concealed trapway
- Installation adjustability: Can accommodate 10" to 12" rough-in incrementally, and allows for approx. 1" of lateral adjustment.
- Premium MaP Certified 800 g
- Watersense Labelled
- ADA Elongated Bowl height 16½"
- Includes 326611W Soft Close - Detachable Seat
- Includes Smart Glaze - Powered by Nano Technology
- Utilizes Caroma®'s Unique *Smart Connect™*

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Caravelle Smart 270 One Piece Easy Height Elongated (Including Seat)	989900	103	
One Piece Toilet and Seat			\$885

Additional Highlights



Smart Connect™

- Fastest, easiest installation method available for toilets with fully skirted bowls
- Eliminates time consuming need to drill holes into flooring





Caravelle Smart One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3L) Dual Flush HET #989900

One Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept one piece toilet featuring a **1.28/0.8 gpf (4.8/3 lpf)** flush volume. **Caravelle Smart One Piece Easy Height Elongated** dual flush high efficiency toilet (HET) is designed to provide a seat height between 17" to 19" (432 to 482mm) measured to the top of the toilet seat for disabled persons. The versatility of the **Caravelle Smart One Piece Easy Height Elongated** toilet makes it ideal for able bodied, ambulant persons with disabilities or for wheelchair users. Designed with smooth rounded contours and a concealed outlet for easy cleaning. **Important:** The Caravelle Smart One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Toilet:** Caravelle Smart One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.
- Tank:** The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications.
- Water Control Valve:** **Standard Bottom Entry** -- available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.
- Weight:** 103 lbs (47.0 kg).
- Fixing:** The one piece toilet is fixed to the floor with corrosion resistant screws and closet bowl guard washers and a fixing assembly kit. Bowl is to be bonded to the floor with an approved silicon caulking.
- Seat:** The soft close detachable elongated seat is included: Code No. 326611W
- Colors:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Caravelle Smart One Piece Easy Height Elongated Toilet:		Code No.
S Trap	LH inlet	989900



HIGH EFFICIENCY TOILET
HET



Note: All height dimensions to underside of closet bowl. Make allowance for bedding.

Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking.




Caravelle Smart 270 One Piece (Lever) Easy Height Elongated

Inspired by Innovation. The redesigned Caravelle Smart 270 One Piece (Lever) High Efficiency Toilet (HET) exemplifies Caroma®'s dedication to simple beauty and Smart Design.

- 1.28/0.8 gallon (4.8/3 litre) dual flush lever handle HET toilet (push lever down for 1.28g/4.8l) flush or pull up for .8g/3l flush
- Available with lever on left (989100W) or right (989900W-R) side of tank
- Large fully glazed, concealed trapway
- Installation adjustability: Can accommodate 10" to 12" rough-in incrementally, and allows for approximately 1" of lateral adjustment.
- Premium MaP Certified at 1000 g; Watersense Labelled
- ADA Elongated Bowl height 16½"
- Includes 326611W Soft Close - Detachable Seat
- Includes Smart Glaze - Powered by Nano Technology
- Utilizes Caroma®'s Unique *Smart Connect™*

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Caravelle Smart 270 One Piece Easy Height Elongated		103	
With Left Hand Lever	989100W		
With Right Hand Lever	989100W-R		
One Piece Toilet and Seat			\$937

Additional Highlights



Smart Connect™

- Fastest, easiest installation method available for toilets with fully skirted bowls
- Eliminates time consuming need to drill holes into flooring

Caravelle Smart One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3L) Dual Flush HET #989100

One Piece Ultra Low Flush (HET)
Vitreous China Washdown Toilet



A modern concept one piece toilet featuring a **1.28/0.8 gpf (4.8/3 lpf)** flush volume. **Caravelle Smart One Piece Easy Height Elongated** left or right lever dual flush high efficiency toilet (HET) is designed to provide a seat height of 17-1/2" (445mm) measured to the top of the toilet seat. The versatility of the **Caravelle Smart One Piece Easy Height Elongated** toilet makes it ideal for able bodied, ambulant persons with disabilities or for wheelchair users. Designed with smooth rounded contours and a concealed outlet for easy cleaning.

Important: The Caravelle Smart One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

Toilet: **Caravelle Smart One Piece Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.

Outlet: Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.

Tank: The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications. Push down side lever for full flush (1.28 gpf / 4.8 lpf) and pull up side lever for reduced flush (0.8 gpf / 3 lpf). Tank with a right hand lever is available.

Water Control Valve: **Standard Bottom Entry** -- available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.





Weight: 103 lbs (47.0 kg).

Fixing: The one piece toilet is fixed to the floor with corrosion resistant screws and closet bowl guard washers and a fixing assembly kit. Bowl is to be bonded to the floor with an approved silicon caulking.

Seat: The soft close detachable elongated seat is included: Code No. 326611W

Colors: White.

Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Caravelle Smart One Piece Easy Height Elongated Toilet:		Code No.
LH Lever	LH inlet	989100W
RH Lever	LH inlet	989100W-R



HIGH EFFICIENCY TOILET
HET



Note: All height dimensions to underside of closet bowl. Make allowance for bedding.

Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking.



Somerton Smart 270 Easy Height Elongated


The ultimate in practical sophistication.

Caroma®'s Somerton Smart 270 is a beautifully simple way to save water without compromising style or performance.

- 1.28/0.8 gallon (4.8/3 litre) Top Mounted two button dual flush high efficiency (HET) toilet
- Features redesigned beautiful new bowl with large fully-concealed trapway
- Installation adjustability: Can accommodate 10" to 12" rough-in incrementally and allows for approximately 1" of lateral adjustment
- Signature Caroma® Trapway is fully glazed and twice the size of the industry standard; virtually eliminates clogging
- ADA Elongated Bowl height 16½"
- Includes 326611W Soft Close - Detachable Seat
- MaP® Certified and Watersense Labelled
- Utilizes Caroma®'s Unique Smart Connect™
- Includes Smart Glaze - Powered by Nano Technology
- Includes Braided Supply Line

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Somerton Smart Tank	810788W	40	\$258
Somerton Easy Height Elongated Bowl (with seat)	829109W	57	\$618
White Tank Bowl and Seat		97	\$876

Additional Highlights



Smart Connect™

- Fastest, easiest installation method available for toilets with fully skirted bowls
- Eliminates time consuming need to drill holes into flooring.


Somerton Smart
Easy Height Elongated
1.28/0.8 gpf (4.8/3 lpf)
Dual Flush HET
Bowl #829109W Tank #810788W

Two Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept close coupled **1.28/0.8 gpf (4.8/3 lpf), Somerton Smart Easy Height Elongated** dual flush washdown toilet designed to provide a seat height of 17-1/2" (445mm) measured to the top of the toilet seat. The closet bowl has been designed with rough-in of **10" (255mm) to 12" (305mm)** provided by an offset outlet connector option. The tank incorporates a high performance barrel type outlet valve which has been specially developed with the Easy Height Elongated bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 lpf) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important. **Important:** The Somerton Smart Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards for Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Closet bowl:** **Somerton Smart Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush washdown closet bowl with box rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) elongated outlet connection.
- Tank:** **Somerton Smart Tank** - has a free lifting lid and is suitable for domestic and light commercial application. 16" long toilet hose connector is included for easy installation.
- Weight:** Bowl Weight 57.2 lbs (26 kg) Tank weight 40 lbs (18.2 kg)
- Water Control Valve:** Standard Bottom Entry Tank -- available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only. 16" long toilet hose connector is included.
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Seat:** The soft close detachable elongated top fixing seat is included: Code No. 326611W.
- Colors:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.






Somerton Smart 270 Lever Handle; Easy Height Elongated

The ultimate in practical sophistication. This Caroma® Somerton Smart 270 features a newly designed bowl and tank with side lever. Large fully-concealed trapway

- 1.28/0.8 gallon (4.8/3 litre) two button dual flush high efficiency (HET) toilet
- Tank is available with lever on left (model 829110W) or the right (model 829110W-R)
- Installation adjustability: Can accommodate 10" to 12" rough-in incrementally and allows for approximately 1" of lateral adjustment
- Signature Caroma® Trapway is fully glazed and twice the size of the industry standard; virtually eliminates clogging
- ADA Elongated Bowl height 16½"
- Includes 326611W Soft Close - Detachable Seat
- MaP Premium Certified at 1000g and Watersense Labelled
- Includes Smart Glaze - Powered by Nano Technology
- Utilizes Caroma®'s Unique Smart Connect™

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Somerton Smart Tank	829110W	40	\$281
Somerton Smart Tank-RH Lever	829110W-R	40	\$281
Somerton Easy Height Elongated Bowl (with seat)	829109W	57	\$618
White Tank Bowl and Seat		97	\$899

Additional Highlights



Smart Connect™

- Fastest, easiest installation method available for toilets with fully skirted bowls
- Eliminates time consuming need to drill holes into flooring.


Somerton Smart Easy Height Elongated 1.28/0.8 gpf (4.8/3 l) Dual Flush HET Bowl #829109 Tank #829110W

Two Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept close coupled **1.28/0.8 gpf (4.8/3 lpf)**, **Somerton Smart Easy Height Elongated** left or right lever dual flush washdown toilet installation designed to provide a seat height of 17-1/2" (445mm) measured to the top of the toilet seat. The closet bowl has been designed with rough-in of **10" (255mm) to 12" (305mm)** provided by an offset outlet connector option. The tank incorporates the high performance barrel type outlet valve which has been specially developed with the Easy Height Elongated bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 lpf) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important. **Important:** The Somerton Smart Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards. For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

- Closet bowl:** **Somerton Smart Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush washdown closet bowl with box rim.
- Outlet:** Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10"(255mm) to 12"(305mm) elongated outlet connection.
- Tank:** **Somerton Tank** - has a free lifting lid and is suitable for domestic and light commercial application. Push down side lever for full flush, and pull up side lever for reduced flush. Tank with a right hand lever is available. 16" long supply flex hose is included for easy installation.
- Weight:** Bowl Weight 57.2 lbs (26 kg) Tank weight 40 lbs (18.2 kg)
- Water Control Valve:** Standard Bottom Entry Tank -- available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only. 16" extra long stainless steel water supply hose is included.
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Seat:** The soft close detachable elongated top fixing seat is included: Code No. 326611W.
- Colors:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.





Sydney Smart Back Outlet Round Front Plus

Innovative Efficiency. The Sydney Smart High Efficiency Toilet (HET) Back Outlet Bowl demonstrates Caroma®'s innovative approach to unique installations. Wash-down technology coupled with an extra large trapway ensures quiet, efficient flushing.

- 1.28/0.8 gallon (4.8/3 litre) two button dual flush HET toilet
- Floor mounted, rear outlet connection is ideal for small bathrooms or where standard floor installation is not recommended
- Caroma® signature trapway is twice the size of industry average, virtually eliminating clogs
- Bowl height 15½"
- MaP Premium certified 900 grams
- Watersense Labelled
- Includes 326201 Soft Close - Round Front Seat in with 609450 Box

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Sydney Smart Tank	622322	30	\$263
Sydney Smart Back Outlet Round Front Plus Bowl with Seat (Includes Back Outlet Connector)	609450	62	\$491
Tank Bowl and Seat		92	\$754

Additional Highlights




Signature Trapway

- At more than twice the size of standard North American trapways, Caroma® eliminates clogging.*
- *It is not waste that typically clogs toilets but paper products. The massive Caroma® trapway has been tested for decades in extreme conditions all over the world with almost perfect success! Clogging a Caroma® bowl would require an unreasonably excessive amount of paper.


Sydney Smart Back Outlet Round Front Plus 1.28/0.8 gpf (4.8/3 lpf) Dual Flush HET Bowl #609450 Tank #622322

Two Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept close coupled **1.28/0.8 gpf (4.8/3 lpf), Sydney Smart Back Outlet** dual flush high efficiency toilet (HET) featuring unique two button activation providing substantial water saving compared to other HET or standard toilets and smooth round contours for easy cleaning. The closet bowl has been designed with a 4" rear outlet rough-in. The tank incorporates a high performance outlet valve which has been specially developed with the Round Front Plus bowl to ensure optimum flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 lpf) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important.

- Closet bowl:** **Sydney Smart Back Outlet Round Front Plus** 1.28/0.8 gpf (4.8/3 lpf) dual flush washdown closet bowl with box rim.
- Outlet:** Floor mounted rear outlet connection. M-14-64-020 Back Outlet Connector and 687230 Foam Wall Gasket are included.
- Tank:** **Sydney Smart Tank** - has a free lifting lid and is suitable for domestic and light commercial applications.
- Weight:** Bowl Weight 62.0 lbs (28.2 kg) Tank Weight 29.7 lbs (13.5 kg)
- Water Control Valve:** Standard Bottom Entry Tank -- available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.
- Fixing:** The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.
- Seat:** The soft closing round top fixing seat is included: Code No. 326201W.
- Colors:** White.
- Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.





Sydney Smart II Easy Height Elongated

Simply incredible performance. The new Sydney Smart II High Efficiency Toilet (HET) combines the power of Caroma® innovation with simplicity of design. Powerful enough for the most demanding commercial setting, innovative enough for any home.

- 1.28/0.8 gallon (4.8/3 litre) two button dual flush HET toilet
- Caroma®'s signature trapway is fully glazed and twice the size of the industry standard, virtually eliminating clogs
- 12" rough in
- ADA Bowl height 16½"
- MaP Premium Labelled 1000 grams
- Includes 326202W Soft Close - Elongated Seat
- Note: Sydney Smart II replaces the Sydney Smart but components of the two models are not interchangeable

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Sydney Smart II Tank	302100W	37	\$211
Sydney Smart II 305 Elongated Bowl with seat	305102W	60	\$394
Tank bowl and Seat		97	\$605

Additional Highlights



Signature Trapway

- At more than twice the size of standard North American trapways, Caroma® eliminates clogging.*

*It is not waste that typically clogs toilets but paper products. The massive Caroma® trapway has been tested for decades in extreme conditions all over the world with almost perfect success! To clog a Caroma® bowl you would have to use an unreasonably excessive amount of paper.

Sydney Smart II 305
Easy Height Elongated
1.28/0.8 gpf (4.8/3 l)
Dual Flush HET

Two Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept close coupled washdown **1.28/0.8 gpf (4.8/3 l) Sydney Smart II 305 Easy Height Elongated** dual flush high efficiency toilet (HET) featuring unique two button activation providing substantial water saving compared to other HET or standard toilets and smooth rounded contours for easy cleaning. The closet bowl has been designed with a **12" (305 mm)** outlet rough-in. The tank incorporates a high performance outlet valve which has been specially developed with the 305 Elongated bowl to ensure optimum flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 l) dual flush system, the toilet is suitable for multi-purpose applications where **water conservation** is important.

Closet bowl: 305 Easy Height Elongated 1.28/0.8 gpf (4.8/3 l) full flush washdown closet bowl with box flushing rim.

Outlet: Floor mounted 12"(305mm) elongated outlet connection.

Tank: **Sydney Smart II Tank** - has a free fitting lid and is suitable for domestic and light commercial applications.

Weight: 100 lbs (45 kg).


Water Control Valve: **Standard Bottom Entry Tank** -- available as left hand inlet and incorporates a super quiet water control assembly. Internal overflow only.

Fixing: The tank is fixed directly to the closet bowl with a robust base fixing system without the need for wall fixing.

Seat: The slow closing elongated seat is included: Code No. 326202W.

Colors: White.

Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.





Sydney Smart II One Piece Easy Height Elongated

Entry Point into precision technology

The Sydney Smart II One Piece reimagines the popular Sydney suite. Now with a fully concealed trapway, top mounted flush buttons and improved flushing performance, the Sydney Smart II One Piece is the perfect addition to any home.

- 1.28/0.8 gallon (4.8/3 litre) dual flush HET toilet with top mounted buttons
- Also available with lever handles, left (987200) or right (987200-R) side of tank
- Signature Caroma® trapway is fully glazed and twice the size of the industry standard, making the Sydney Smart II One Piece virtually uncloggable
- Installation adjustability: Can accommodate 10" to 12" rough-in incrementally and allows for approximately 1" of lateral adjustment
- ADA Elongated Bowl height 16½"
- Watersense Labelled and MaP Premium certified
- Includes 326202W Soft close Seat
- Includes Smart Glaze
- Utilizes Caroma®'s Unique *Smart Connect™*

DESCRIPTION	CODE	WEIGHT (LBS)	CDN LIST
Sydney Smart II One Piece Easy Height Elongated With Top buttons	987150	103	
One Piece Toilet and Seat			\$839

Additional Highlights



Signature Trapway

- The Signature Caroma® trapway is fully glazed and more than twice the size of the industry standard, eliminating clogging.*
- *It is not human waste that typically clogs toilets, it is paper products. The massive Caroma® trapway has been tested for decades in extreme conditions all over the world with almost perfect success! To clog a Caroma® bowl you would have to use an unreasonably excessive amount of paper.

Sydney Smart II One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3L) Dual Flush HET #987150

One Piece Vitreous China Washdown Toilet



A modern concept one piece toilet featuring a **1.28/0.8 gpf (4.8/3 lpf)** flush volume. **Sydney Smart II One Piece Easy Height Elongated** dual flush high efficiency toilet (HET) is designed to provide a seat height between 17-1/2" (445mm) measured to the top of the toilet seat. The versatility of the **Sydney Smart II One Piece Easy Height Elongated** toilet makes it ideal for able bodied, ambulant persons with disabilities or for wheelchair users. Designed with smooth rounded contours and a concealed outlet for easy cleaning.

Important: The Sydney Smart II One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

Toilet: **Sydney Smart II One Piece Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.

Outlet: Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.

Tank: The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications.





Water Control Valve: **Standard Bottom Entry** -- available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.

Weight: 103 lbs (47.0 kg).

Fixing: The one piece toilet is fixed to the floor with corrosion resistant screws and closet bowl guard washers and a fixing assembly kit. Bowl is to be bonded to the floor with an approved silicon caulking.

Colors: White.

Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Sydney Smart II One Piece Easy Height Elongated Toilet:		Code No.
S Trap	LH inlet	987150



HIGH EFFICIENCY TOILET
HET



Note: All height dimensions to underside of closet bowl. Make allowance for bedding.

Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking.



Sydney Smart II One Piece Easy Height Elongated

Elegance reimagined

The Sydney Smart II One Piece reimagines the popular Sydney suite. Now with a fully concealed trapway, side lever handle and improved flushing performance, the Sydney Smart II One Piece is the perfect addition to any home.

- 1.28/0.8 gallon (4.8/3 litre) dual flush lever handle HET toilet; (push lever down for 1.28g/4.8l flush or pull up for 0.8g/3l flush)
- Available with lever on left (987200) or right (987200-R) side of tank
- Signature Caroma® trapway is fully glazed and twice the size of the industry standard, making the Sydney Smart II One Piece virtually uncloggable
- Installation adjustability: Can accommodate 10" to 12" rough-in incrementally and allows for approximately 1" of lateral adjustment
- ADA Elongated Bowl height 16½"
- Watersense Labelled and MaP Premium certified at 1000g
- Includes 326202 Soft close Seat
- Utilizes Caroma®'s Unique *Smart Connect™*

DESCRIPTION	CODE	WEIGHT (LBS)	CDN LIST
Sydney Smart II One Piece		103	
Easy Height Elongated With			
Left Side Lever	987200		
With Right Side Lever	987200-R		
One Piece Toilet and Seat			\$868

Additional Highlights



Signature Trapway

- The Signature Caroma® trapway is fully glazed and more than twice the size of the industry standard, eliminating clogging.*
- *It is not human waste that typically clogs toilets, it is paper products. The massive Caroma® trapway has been tested for decades in extreme conditions all over the world with almost perfect success! To clog a Caroma® bowl you would have to use an unreasonably excessive amount of paper.

Sydney Smart II One Piece Easy Height Elongated 1.28/0.8 gpf (4.8/3L) Dual Flush HET #987200

One Piece Ultra Low Flush (ULF)
Vitreous China Washdown Toilet



A modern concept one piece toilet featuring a **1.28/0.8 gpf (4.8/3 lpf)** flush volume. **Sydney Smart II One Piece Easy Height Elongated** left or right lever dual flush high efficiency toilet (HET) is designed to provide a seat height of 17-1/2" (445mm) measured to the top of the toilet seat. The versatility of the **Sydney Smart II One Piece Easy Height Elongated** toilet makes it ideal for able bodied, ambulant persons with disabilities or for wheelchair users. Designed with smooth rounded contours and a concealed outlet for easy cleaning.

Important: The Sydney Smart II One Piece Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards For Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

Toilet: **Sydney Smart II One Piece Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) dual flush box rim.

Outlet: Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for 10" (255mm) to 12" (305mm) rough-in.

Tank: The tank is an integral part of the toilet with a free fitting lid and is suitable for domestic and light commercial applications. Push down side lever for full flush (1.28 gpf / 4.8 lpf) and pull up side lever for reduced flush (0.8 gpf / 3 lpf). Tank with a right hand lever is available.

Water Control Valve: **Standard Bottom Entry** -- available as left hand inlet which incorporates a super quiet water control assembly. Internal overflow only.





Weight: 103 lbs (47.0 kg).

Fixing: The one piece toilet is fixed to the floor with corrosion resistant screws and closet bowl guard washers and a fixing assembly kit. Bowl is to be bonded to the floor with an approved silicon caulking.

Seat: The soft close detachable elongated seat is included: Code No. 326611W

Colors: White.

Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Sydney Smart II One Piece Easy Height Elongated Toilet:		Code No.
LH Lever	LH inlet	987200
RH Lever	LH inlet	987200-R



Note: All height dimensions to underside of closet bowl. Make allowance for bedding.

Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking.




Caroma Commercial Open-Front Elongated Seat

A heavy duty elongated seat suitable for all commercial and industrial applications.

- Bottom Fixing
- Self Sustaining Hinges hold seat in a raised position
- Sturdy Polypropylene construction resists staining, fading, chipping and peeling
- Engineered to ensure excellent fit and comfort
- Sturdy metal hinge system
- No Cover
- Two Year Warranty

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
White	326060W	5	\$93






Caroma Soft Closing Round-Front Plus Seat

A soft-closing seat designed and engineered to perfectly fit Caroma Round Front Plus toilet bowls

- Soft Close technology prevents the lid from slamming down. Lid always closes softly and quietly
- Top Fixing for ease of installation and maintenance
- Sturdy Polypropylene construction resists staining, fading, chipping and peeling
- Engineered to ensure excellent fit and comfort
- Discreet, color matched plastic hinge system
- Two Year Warranty

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
White	326201W	5	\$80






Caroma Soft Closing Elongated Seat

A soft-closing seat designed and engineered to perfectly fit Caroma elongated toilet bowls

- Soft Close technology prevents the lid from slamming down. Lid always closes softly and quietly
- Top Fixing for ease of installation and maintenance
- Sturdy Polypropylene construction resists staining, fading, chipping and peeling
- Engineered to ensure excellent fit and comfort
- Discreet, color matched plastic hinge system
- Two Year Warranty

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
White	326202W	5	\$83






Caroma Soft Closing Detachable Elongated Seat

A luxurious soft-closing, detachable seat designed and engineered to perfectly fit Caroma elongated toilet bowls

- Soft Close technology prevents the lid from slamming down. Lid always closes softly and quietly.
- Designed to instantly detach, allowing for fast and easy cleaning
- Top Fixing for ease of installation and maintenance
- Sturdy Polypropylene construction resists staining, fading, chipping and peeling
- Engineered to ensure excellent fit and comfort
- Two Year Warranty

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
White	326611W	5	\$99





Caroma® Cube II Undermount Basin

The Cube II under counter basin offers strong square angles, slim walls and softened edges; a beautiful striking design option that adds luxury and efficiency to all bathroom environments.

The Cube II vanity basin blends a sharp contemporary look with a warm, welcoming feel.

21 1/2" X 13" (545 mm X 330 mm)

Available with No Hole only, suitable for counter mount or wall mount faucets

· Drain opening 1 1/4" (32 mm)

· Available in White Only

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Cube Undermount - No Hole	760502W	27	\$209

Complimentary Products



- Caroma® basins blend seamlessly with Caroma HET high efficiency, dual flush toilet suites.
- Shown are the Caravelle Smart One Piece with side lever (989100) and the Invisi Series II Somerton Wall Hung Bowl (604100W)

cube II

Ceramic Under Counter Vanity Basin #760502

Basin Size: 545mm x 330mm (21-1/2" x 13")



Offering strong square angles, slim walls and softened edges, Cube II is a striking design option for the modern bathroom. While the Cube under counter vanity basin blends the sharpest contemporary looks with a welcoming feel, it provides a generous bowl area. The basin is suitable for general purpose domestic and commercial applications. The rim is sealed to the underside of the counter top with an acetic cured silicone sealant.

Faucet Holes: Basin available as no faucet hole Code No.760502.

Waste Outlet: The waste drain is not included in the carton box, but is available in the following options for purchase:
FA725 -- Chrome Plated
FA725BN -- PVD Brushed Nickel Finish
FA725PN -- PVD Polished Nickel Finish


Overflow: Only available with Overflow. Designed for maximum tap flow rate of 15 litres/minute.

Fixing: Bracket clips #813734 are supplied as standard for fixing basin to marble or granite counter tops. Four brackets are supplied with each basin and must be fixed to the underside of the counter top with appropriate fasteners.

The rim of the basin must be sealed to the counter top with an acetic cured silicone sealant. Epoxy type glues must not be used. The basin is supplied with a template which must be used for the counter top cut-out.

Colors: White only.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.





Liano Above Counter Basin

The Liano basin series was created for the designer market and prestige projects. An Architectural minimalist style was adopted for the Liano square styling with generous bowl size and distinct faucet platform.

The Liano Above Counter Basin sits stylishly on top of counter, allowing for either wall mounted or counter mounted basin faucets

- Impeccably finished Vitreous China
- 16.5" (420 mm) X 18.5" (470 mm) outside dimensions
- Available with No Faucet holes for wall or countertop faucet option, or with single or 3-Hole options
- Drain opening 1 1/4" (32 mm)
- Available in White Only

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
No Hole Option	664408W	31	\$399
1-Hole Option	664418W	31	\$399
3-Hole, 8 Inch Centre	664438W	31	\$399

Complimentary Products



- Caroma basins blend seamlessly with Caroma HET high efficiency, dual flush toilet suites.
- Shown are Caravelle Smart One Piece (989900) and Sydney Smart 305 One Piece.(828908W).

Liano Above Counter

Vitreous China Lavatories/Sinks

Lavatory Size: 16¹/₂" (420mm) x 18¹/₂" (470mm) (nominal)



The **Liano Above Counter** lavatory has been designed to meet the needs of the designer market for prestige projects. An architectural minimalist style was adopted for the square Liano incorporating a generous bowl area and distinctive tapware platform. The rim is sealed to the countertop with an acetic cured silicon caulking.

Faucet Holes: Lavatory available in no faucet hole option Code No. 664408, one faucet hole – centre option Code No. 664418, and three faucet hole option Code No. 664438.

Drain Outlet: Drain outlets use 1¹/₄" (32mm) diameter drain outlet assemblies.

Bowl Capacity: 1.26 gal (4.8 l) to overflow.

Weight: 31 lbs (14 kg)

Overflow: Rear overflow.


Fixing: The underside of the lavatory rim must be sealed to the countertop with an approved acetic cured silicon caulking. **Epoxy type glues must not be used.** The lavatory is supplied with a template which must be used for the countertop cut-out.

Color: White.

Dimension: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

c-UPC®

IAPMO listed for USA & Canada





Liano Semi Recessed Basin

The Liano Series was created for the design market with prestige projects in mind. An Architectural minimalist style was adopted for the Liano featuring square styling, generous bowl size and a distinct faucet platform.

The Liano Semi Recessed Basin overhangs the vanity slightly, allowing for more countertop space and easier access to the faucet.

Impeccably finished Vitreous China

- 16.5" (420 mm) X 18.5" (470 mm) outside dimensions
- Perfect for Smaller Spaces or Double Basin Bathroom designs
- Available with single or 3-Hole options
- Drain opening 1 1/4" (32 mm)
- Available in White Only

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
1-Hole Option	661218W	31	\$399
3-Hole, 8 Inch Centre	661238W	31	\$399

Complimentary Products



- Caroma basins blend seamlessly with Caroma HET high efficiency, dual flush toilet suites.
- Shown are Caravelle Smart One Piece (989900) and Sydney Smart 305 One Piece.(828908W).

Liano Semi-Recessed

Ceramic Lavatories/Sinks

Lavatory Size: 16¹/₂" (420mm) x 18¹/₂" (470mm) (nominal)



c-UPC®

IAPMO listed for USA & Canada

The **Liano Semi-Recessed** lavatory has been designed to meet the needs of the designer market for prestige projects. An architectural minimalist style was adopted for the square **Liano** incorporating a generous bowl area and distinctive tapware platform. The lavatory is sealed to the countertop with an approved acetic cured silicon caulking.

Faucet Holes: Lavatory available in one faucet hole – centre option Code No. 661218 and three faucet hole – 8" option Code No. 661238.

Drain Outlet: Drain outlets use 1¹/₄" (32mm) diameter drain outlet assemblies.

Bowl Capacity: 1.26 gal (4.8 l) to overflow.

Weight: 31 lbs (14 kg).


Overflow: Rear overflow.

Fixing: **D.250 Bracket with Tie Hooks:** Supplied. Recommended for domestic and general commercial use. Two D.250 brackets are fixed to the underside of the counter top to secure the tie hooks which anchor the back of the lavatory to the counter top. The lavatory must be sealed to the top and front surface of the counter with an approved acetic cured silicon caulking. **Epoxy type glues must not be used.** The lavatory is supplied with a template which must be used for the countertop cut-out.


Important: For granite or marble tops, fix two 1" (20mm) thick wooden blocks in the bracket position on the underside of the granite/marble with fast setting two part epoxy. When fully set, screw the brackets into position on the wooden blocks. Other suitable fastening systems maybe used.

Color: White.


Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Variable when using D. 250 Tie Brackets.
Note: Local authorities have requirements for minimum lavatory to wall dimensions.



D.250 Tie Bracket





Liano Undermount Basin

The Liano under counter basin features a modern, simple crisp style with geometric bowl and gently curved depth. With its unique contemporary appearance, Liano is ideally suited to prestige bathroom projects, be they commercial or domestic. Impeccably finished Vitreous China

- 17" X 17" (430 mm X 430 mm) outside dimensions, perfect for smaller spaces or double basin designs.
- Available with No Hole only, suitable for counter mount or wall mount faucets
- Drain opening 1 1/4" (32 mm)
- Available in White Only

DESCRIPTION	CODE	WEIGHT (LBS)	CDN. LIST
Liano Undermount - No Hole	664208W	21	\$214

Complimentary Products



- Caroma basins blend seamlessly with Caroma HET high efficiency, dual flush toilet suites.
- Shown are Caravelle Smart One Piece (989900) and Invisi Cube Series II Wall Hung bowl (604300W)

Liano Under Counter

Vitreous China Lavatories/Sinks

Lavatory Size 17" (430mm) x 17" (430mm) (nominal)



c-UPC®

IAPMO listed for USA & Canada

The **Liano Under Counter** lavatory has been designed to meet the needs of the designer market for prestige projects. An architectural minimalist style was adopted for the square **Liano**. The lavatory is suitable for general purpose applications. The rim is sealed to the underside of the countertop with an acetic cured silicon caulking.

Faucet Holes: Available in no faucet hole Code No. 664208. The lavatory is intended for use with counter top or wall mounted tapware.

Drain Outlet: Drain outlets use 1 1/4" (32mm) diameter drain outlet assemblies.

Installation: The Liano Under Counter is suitable for installation under polyester, marble, natural stone, or other suitable impervious materials.

Bowl Capacity: 2.9 gal (9 l) to overflow.


Weight: 21 lbs (10 kg).

Overflow: Rear overflow.

Fixing: **Aluminium Clip Bracket** Code No. 813734 supplied as standard for fixing lavatory to marble or granite countertops. **Alloy Bracket** Code No. 811326 (not supplied) is available as an option for fixing lavatory to wooden counter tops. Four brackets are supplied with each lavatory and must be fixed to the underside of the countertop with appropriate fasteners. The rim of the lavatories must be sealed to the countertop with an approved acetic cured silicon caulking. **Epoxy type glues must not be used.** The lavatory is supplied with a template which must be used for the countertop cut-out.

Color: White.

Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Conditions of Sale

Conditions of Sale

1. General

- (a) Only these Terms and Conditions of Sale ("Terms and Conditions"), as may be varied under clause 1(c), govern the sale and purchase of Goods described in the Quotation issued by Company to Customer, and bind the Company. All other Terms and Conditions (including Customer's conditions of purchase, if any), warranties and representations are excluded and do not bind the Company.
- (b) Agents or distributors of the Company's Goods have no power, right or authority, express or implied, to bind the Company.
- (c) The Company may vary these Terms and Conditions at its discretion and without notice.
- (d) A Quotation given to Customer is not an offer, and is valid only insofar as the Quotation constitutes terms for consideration for 90 days from the date of Quotation, or as otherwise stated.
- (e) An order placed by Customer under a Quotation is not binding on the Company until accepted in writing by the Company. That acceptance by the Company of Customer's Quotation shall be effective to form a contract between the Company and Customer pursuant to the Company's acceptance and to the Terms and Conditions herein.

2. Price

- (a) Prices for Goods will be as per the Company's Official Price List.
- (b) Prices may be altered by the Company at any time.
- (c) Applicable taxes, delivery charges and extra (packaging) surcharges are payable by Customer.
- (d) The Company may impose a handling and delivery charge on low value orders.
- (e) Prices for the Goods specified on the Company's Official Price List are exclusive of all city, state and federal excise taxes, including, without limitation, taxes on manufacture, sales, receipts, gross income, occupation, use and similar taxes. Customer agrees to pay such taxes directly or to reimburse the Company for all such taxes, whether imposed on Customer, required to be collected by the Company or imposed on the Goods or on Customer in connection with this sale. Wherever applicable, such tax or taxes shall be added to the invoice as a separate charge or invoiced separately. Customer agrees to pay all personal property taxes that may be levied against the Goods after the date of delivery.

3. Orders and Delivery

- (a) Orders for Goods cannot be suspended or cancelled except with the Company's consent. Customer shall pay all reasonable expenses incurred by the Company due to suspension or cancellation.
- (b) Delivery Dates are estimates only and the Company is not liable for any loss or damage for failure to deliver by those dates. The Company shall not be liable for, nor shall the Company be in breach of its obligations to Customer because of, any delivery made within a reasonable time after the stated Delivery Date.
- (c) The Company may make partial deliveries of any order and render an invoice to Customer for the Goods delivered. Failure to make delivery of the total order will not invalidate the sale of Goods delivered.

4. Returns

- (a) Goods are sold on a non-return basis and unless damaged (refer to clause 8) or incorrectly delivered (refer to clause 3) cannot be returned.
- (b) All returns must receive the prior approval of the Company.
- (c) The Company reserves the right to inspect Goods to be returned.
- (d) Goods must be returned according to the Company's procedure for returns for credit or replacement.
- (e) Customer must retain signed return documentation as proof of a return.
- (f) Unless damaged or incorrectly delivered, a re-stocking fee of 20% applies to all Goods returned and is payable within 30 days of the end of the month in which the credit is issued. Additional charges may apply for damaged or incomplete packaging.

5. Payment

- (a) Customer must pay the Invoice Value within 30 days of the date of the invoice (i.e. net 30 days).
- (b) Any Goods returned or to be returned by Customer under clause 4 do not alter the payment terms on an invoice.
- (c) The Company may impose a service charge of up to 1 1/2% per month (calculated on daily balances) on overdue amounts.
- (d) Customer shall be liable for all costs incurred by the Company in recovering outstanding monies from Customer, including collection agency fees, court costs and bank dishonour fees.
- (e) If any payment is overdue, the Company reserves the right to suspend any other deliveries to Customer.

6. Risk and Ownership of Goods

- (a) Risk of loss or damage to products purchased by Customer shall pass to Customer when the products are delivered FCA from an SSI warehouse. Notwithstanding the foregoing, title to any such products will not pass from Company to Customer until the purchase price is fully paid. Customer grants Company a security interest in all such products until Company receives payment of the total fees for such products. Customer shall, at the request of Company, execute and deliver to Company any instruments (including Uniform Commercial Code financing statements) that Company may deem

Conditions of Sale

Conditions of Sale

necessary to protect its security interest in such products.

- (b) Customer will assume and not be released from its obligation to pay the full purchase price in the event of any damage, loss, or destruction of the products after delivery as described herein. Claims for shortages attributable to Company must be in writing and received by Company within 14 (fourteen) days after delivery, and must be accompanied by Company's packing slip and full, detailed description of any such claim.

7. Damage, Shortage, Loss In Transit and Defective Goods

- (a) Unless otherwise agreed, Customer must advise the Company of any damaged or shortage of Goods within 48 hours after the Delivery Date, otherwise no liability will be accepted.
- (b) Goods subsequently found to be defective must be reported immediately when the defect is discovered and any reported defects shall be supported with pictures and documentation

8. Limitation of Liability

- (a) Unless otherwise agreed, damaged Goods (excluding unavoidable imperfections) will be credited or replaced if the Company is advised within 14 days after the Delivery Date, and the damaged Goods are made available for inspection and return to the Company may elect to:
 - (i) replace the damaged Goods; or
 - (ii) pay the cost of obtaining equivalent products; or
 - (iii) pay the cost of having the damaged Goods repaired.
- (b) In no event shall the Company be liable for any special, incidental, exemplary, punitive or consequential loss, indirect costs or damages including without limitation, litigations costs, installation and removal costs, re-procurements or replacement costs, loss of data, production, opportunity, goodwill or profit arising from any cause whatsoever, regardless of the form of the action, whether in contract, tort (including negligence), strict liability, or otherwise, even if advised of the possibility of such costs or damages.

9. Trademarks

- (a) Customer cannot use the Caroma trademarks and trade names without the prior written approval of the Company.
- (b) All right, title and interest in and to the intellectual property and other proprietary rights embodied in the Goods shall be retained by Caroma. No right or license therein is transferred to the Customer under these Terms and Conditions. Caroma reserves all rights in such intellectual property and other proprietary rights.

10. Changes to Specifications; Discontinuance

The Company reserves the right to make any changes in the specifications of the Goods that do not materially alter their quality or performance, or where change is necessary to conform to any applicable safety or other statutory requirements. The Company also reserves the right to discontinue the sale of the Goods at any time, in its sole absolute discretion.

11. Explanatory Material

- (a) Explanatory Material provided to Customer does not bind the Company, and does not constitute any form of representation by the Company.
- (b) The Company may amend its Explanatory Material without notice to Customer.

12. Non Performance

The Company is not responsible for any lack of operation or performance of the Goods (and any loss or damage) where they are:

- (a) used or adapted for a purpose for which they were not designed;
- (b) combined or integrated with other products not manufactured by the Company.

13. Force Majeure

The Company is not liable for any failure to comply with these conditions where the failure is due to circumstances which are not directly within the Company's control or force majeure, including, but not limited to, acts of terrorism, natural disaster, industrial action, or a failure of a supplier, public utility or common carrier.

14. Taxes

- (a) Customer will be liable for applied taxes on any taxable supply by the Company to Customer.
- (b) The Company reserves the right to raise tax adjustment notes and recipient tax invoices when necessary.
- (c) Customer must supply the Company with its tax registration number (where applicable) prior to or at the time of placing an order with the Company.

15. Waiver

No failure by the Company to enforce or take advantage of any provision hereof shall constitute a waiver of the right

Conditions of Sale

Conditions of Sale

subsequently to enforce or take advantage of such clause or any other clause hereof.

16. Governing Law

The laws of the Province of British Columbia, Canada shall govern in all respects as to the validity, interpretation, construction and enforcement of these Terms and Conditions, without reference to conflicts of laws principles. The U.N. Convention on Contracts for the sale of International Goods shall not apply.

17. Entirety of Agreement

These Terms and Conditions set forth the entire understanding and agreement of the parties with respect to the subject matter hereof and supersede all other oral or written representations and understandings. These Terms and Conditions may only be amended or modified per clause 1(c).

18. Privacy Act

Customer agrees to the Company obtaining information about the financial standing and credit worthiness of Customer.

19. Definitions

Company: SSI™ Sustainable Solutions International, but shall not include any director, officer, employee, agent or representative of the company for any purpose whatever.

Customer: the person or company named in the sales invoice or Quotation issued for the Goods by the Company.

Delivery Date: the date on which the Goods are delivered to Customer.

Invoice Value: the amount stated in the Company's invoice for Goods ordered by Customer.

Explanatory Material: drawings, specifications, explanatory literature and any other materials prepared by the Company for descriptive or explanatory purposes.

Goods: those goods ordered by Customer from the Company from time to time.

Official Price List: the list of prices of Goods set out in the Company's price book or price file or price notifications from time to time.

Price: the price for Goods contained in the Official Price List.

Quotation: a quotation submitted by the Company to Customer for Goods.

Warranty

Guarantee of Product — North America

TWO-YEAR LIMITED WARRANTY

CAROMA plumbing products are warranted to be free of defects in material and workmanship for two years after their initial purchase. This limited warranty applies only to the original purchaser and installation of these products. In the event of a limited warranty claim, proof of purchase from an authorized reseller will be required – save sales receipt.

Sustainable Solutions International (SSI) will, at its election, repair, replace or make appropriate adjustment where our inspection discloses any such defects occurring in normal usage within two (2) years after purchase. SSI is not responsible for removal or installation costs or shipping costs. Warranty parts may be picked up at SSI offices and warehouses. Use of in-tank toilet cleaners will void the warranty.

This limited warranty is void if the product has been moved from its initial place of installation; if it was not installed in accordance with SSI's instructions; or if it has been used or modified in a manner inconsistent with the product as shipped by SSI or adapted for a purpose for which it was not designed. Standard product maintenance such as periodic seal replacement is not considered a defect and is the responsibility of the purchaser.

WARRANTY CONTACT INFO

For service under these warranties, it is suggested that a claim be made through the contractor or dealer from or through whom the product was purchased, or that a service request (including a description of the product model and of the defect and a copy of the sales receipt) be sent to the following address:

SSI Sustainable Solutions International
8395 Riverbend Court
Burnaby BC. V3N 5E7
Attention: Warranty Request
Toll Free Telephone: 1-800-460-7019

Implied warranties including that of merchantability and fitness for a particular purpose are expressly limited in duration to the duration of this warranty. SSI and/or seller disclaim any liability for special, incidental or consequential damages. SSI shall not be liable for any loss, damage, expense or inconvenience of any kind incurred, sustained or suffered by any purchaser as a result of any defect or default in the Caroma product to which this warranty relates.

Some states/provinces do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of special, incidental or consequential damages, so these limitations and exclusions may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state/province to state/province.

Notes:



Caroma is distributed in North America by
Sustainable Solutions International

Telephone: (604) 430 2020

Fax: (604) 430 5050

Toll Free: (800) 460 7019

www.sustainablesolutions.com

